

# ANSI Standard Series

## Ceramic Bushing Insulators



1/208



8.7/40



1/800



Spade Style



Eyebolt Style

### Description

Low Voltage Power Transformer Bushing in accordance with the ANSI/NEMA standards.

1.2 kV-30 kV BIL, 1.2 kV-45 kV BIL,

- 1.2KV (16/21 Eyebolt) Power Transformer Bushing

- 1.2KV Spade Style Power Transformer Bushing

High Voltage Power Transformer Bushing in accordance with the ANSI/NEMA standards.

15kV-95kV BIL, 18kV-125kV BIL, 25kV-150kV BIL, 34.5kV-200kV BIL, 8.7kV-75kV BIL

We are also manufacture and supply various type of Terminal and Conductor for bushing.

### Specifications

Part Number	U.m (kV)	I <sub>r</sub> (A)	Tank Hole Size (mm)	Shield	CD (mm)	BIL (kV)	Stem Connect
<b>ANSI 1/125</b>	1	125	36.5	-	35	30	3/8"-16 UNC
<b>ANSI 1/208</b>	1	208	36.5	-	35	30	1/2"-13 UNC
<b>ANSI 1/417</b>	1	417	71	-	50	30	5/8"-11 UNC
<b>ANSI 1/625</b>	1	625	71	-	50	30	3/4"-10 UNC
<b>ANSI 1/800</b>	1	800	71	-	50	30	1"-14 UNC
<b>ANSI 1/1200</b>	1	1200	71	-	50	30	1-1/4"-12 UNC
<b>ANSI 8.7/40</b>	8.7	40	71	-	145	75	-
<b>ANSI 15/50</b>	15	50	71	5	310	95	-
<b>ANSI 18/50</b>	18	50	71	8	480	125	-
<b>ANSI 27/50</b>	27	50	71	12	830	150	-